Blockout Heavy FR

Igepa-Code-Nr. SBPR-BPREMFRB1

Description

Coated PVC-Banner, for double-sided printing, REACH compliant

Application Short & midle-life advertising

Technical Data Support Cloth (DIN 60001) 100% PES, high tenacity yarn Type of coating (DIN 60001) PVC on both sides Yarn (denier) 500 x 500 dtex Structure 28 x 28 (sq.inch) Total weight 650 g/m2 Tensile strength (DIN 53354) 2009/1617 N/5cm Tear resistance (DIN 53356) 225/196 N/5cm Sutable temperature (DIN 53361) -25 to +70°C Adhesion (DIN 53357) 68 N/5cm Available widths 220 - 320cm, other widths available on request	
Support Cloth (DIN 60001)	100% PES, high tenacity yarn
Type of coating (DIN 60001)	PVC on both sides
Yarn (denier)	500 x 500 dtex
Structure	28 x 28 (sq.inch)
Total weight	650 g/m2
Tensile strength (DIN 53354)	2009/1617 N/5cm
Tear resistance (DIN 53356)	225/196 N/5cm
Sutable temperature (DIN 53361)	-25 to +70 [°] C
Adhesion (DIN 53357)	68 N/5cm
Available widths	220 - 320cm, other widths available on request
Roll lenghts	Standard: 50lm, other lenghts available on request
Flame retardant	B1

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intedend only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

