

MediaTac™ is a 0.5 mil (12µ) clear PET film, coated on both sides with a pressure sensitive acrylic adhesive, one of which is protected by a bleached clay coated Kraft paper siliconized on both sides with a differential release. The adhesive is self-wound on the release liner.

- DEVELOPED FOR PHOTO LABS WHERE A HIGH GRADE OF MOISTURE STABILITY WITHIN THE MOUNTING FILM IS REQUIRED
- IDEAL FOR HIGH-VOLUME MOUNTING, INCLUDING PRE-COATING BOARDS AND IMAGE DECAL APPLICATIONS
- RECOMMENDED FOR MOUNTING PRINTS TO SMOOTH, POROUS SUBSTRATES, SUCH AS WHITE DISPLAY BOARD, FOAM BOARDS, GATORFOAM™ AND TEMPERED HARDBOARD

### PRODUCT STRUCTURE

<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Film</b>	Clear PET
<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Side Clay Coated, 2 Side Siliconized Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	0.5 mil (12µ)	2.5 mil (62µ)
<b>Adhesive Layer</b>	1 mil (25µ) on each side	
<b>Film/Adhesive Ratio</b>	1:0.5:1	
<b>UV Protection Factor</b>	Not Applicable	
<b>Outdoor Durability</b>	Not Applicable	
<b>Service Temperature Range</b>	-4°F to 248°F (-20°C to 120°C)	
<b>Shelf Life</b>	1 year	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

For more information,  
performance and warranty  
guidelines please contact your  
local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.

**DRYTAC®**  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013