

## POSTER PAPER GOLD, Matt

A special inkjet photo medium with a highly absorbative matt inkjet coating on one side of a 127 µm photobased paper. The proprietary photobase paper exists of a paper base with on both sides a polymeric barrier. The product can be laminated and mounted with normal high quality adhesive films (up to 85°C).

To prevent gas fading (colour degradation by air pollutants), it is recommended to laminate the material soon after printing.

Main applications	Retail point of purchase Posters High quality CAD and GIS mapping
Features	Compatible with most pigment and dye based inks Very quick dry times Water resistant Long lasting images Excellent lamination
Availability	30 m rolls in 24", 36", 42", 50", 54" and 60"
Weight	170 g/m <sup>2</sup>
Opacity	94% min. per TAPPI T-425
Caliper	160 µm
Whiteness	100 per CIE Ganz 82
Smoothness, Sheffield	100 nominal per TAPPI T-538
Optimal print conditions	Between 15° - 30°C ; 30% - 70% RH
Shelf life	2 years
Storage conditions	Temperature 10 – 30°C, 30 - 70% RH Allow material to adapt to room conditions, repack open rolls

Arkwright believes that the stated information is reliable. This information is intended for use by persons having technical skill at their own discretion. Since conditions of use are outside of Arkwright's control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

Arkwright-Europe BV  
P.O. Box 220, 5900AE Venlo, The Netherlands  
Telephone: +31 77 320 9020 Fax: +31 77 382 5175  
E-mail: sales@arkwright-eur.com www.arkwright.com