## EasyMesh Liner

Igepa-Code-Nr. SBFX-SBMLR

**Description** Coated PVC Mesh with liner, highly durable, REACH compliant

**Application** short-life advertising

Technical Data	
Support Cloth (DIN 60001)	100% PES
Type of coating (DIN 60001)	PVC on both sides
Yarn (denier)	1000 x 1000
Structure	12 x 12 (sq.inch)
Total weight	370 g/m2
Tensile strength (DIN 53354)	1250/1400 N/5cm
	200 (200 ) (7
Tear resistance (DIN 53363)	300/300 N/5cm
Air Dames a bilita	2670 Har? Inc. (CD/T 5452 4007)
Air Permeability	2678 l/m²/sec. (GB/T 5453-1997)
Sutable temperature (DIN 53361)	-20 to +50 <sup>0</sup> C
Sutable temperature (DIN 33301)	-20 to +30 C
Available widths	190cm - 210cm - 250cm - 320cm
Transact Traditio	250011 220011 320011
Roll lenghts	Standard: 50m, other lenghts available on request
	otaliaa a ooni, otila tallaala on request

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intedend only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

