

# REFLECTIVE BANNER

<b>Igepa-Code-Nr.</b>	SBFX-SBREF5
<b>Description</b>	Semi-coated reflective PVC-Frontlit, highly durable, REACH compliant
<b>Application</b>	midle-life advertising

## Technical Data

<b>Support Cloth (DIN 60001)</b>	100% PES, high tenacity yarn
<b>Type of coating (DIN 60001)</b>	PVC on one side / reflective vinyl on one side
<b>Yarn (denier)</b>	500*500D
<b>Structure</b>	9 x 9 (sq.inch)
<b>Total weight</b>	510 g/m <sup>2</sup>
<b>Tensile strength (DIN 53354)</b>	777/577 N/5cm
<b>Tear resistance (DIN 53356)</b>	177/130 N/5cm
<b>Adhesion (DIN 53357)</b>	45 N/5cm
<b>Sutable temperature (DIN 53361)</b>	-20 to +60°C
<b>Available widths</b>	320cm - other widths available on request
<b>Roll lenghts</b>	Standard: 50lm, other lenghts available on request
<b>Degree of revlectivity</b>	Obervation angle 0,2* / Entrance angle 30* / 170 cd/lx . m <sup>2</sup>

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are inteded only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

