### **Roland Professional Print Management Software Included**









Roland VersaWorks\* supports Adobe\* Illustrator\*, CoreIDRAW\* and other popular design software packages. Choose from a wide variety of layout functions includes scaling, cropping, rotating, auto layout and tiling to optimize your print media. VersaWorks also features Roland Color System Libraries for accurate color matching of traditional and metallic colors, and variable data printing which allows you to efficiently create a series of signs, labels and name badges in which the text and graphics change from one print to the next.

Roland VersaWorks System Requirements			
Operating system	Windows® 7 Professional/Ultimate (32-bit); Windows Vista® Business/Ultimate (32-bit); Windows® XP Professional Service Pack 2 or later (32-bit)		
CPU	Core™2 Duo, 2.0 GHz or faster recommended		
RAM	2 GB or more recommended		
Video card and monitor	A resolution of 1,280 x 1,024 or more recommended		
Free hard-disk space	e 40 GB or more recommended		
Hard-disk file system	system NTFS format		
Optical drive	DVD-ROM drive		

#### Application software compatible with Cutting and Print&Cut

Adobe® Illustrator® 10, CS, CS2, CS3, CS4, CS5 / CoreIDRAW® 11, 12, X3, X4, X5

#### R-Works Easy-To-Use Roland Design Software Included

R-Works allows you to immediately start designing graphics for the BN-20, even if you do not have any design software of your own. With R-Works, you can quickly import commercially-available stock photos or personal photos taken with a digital camera. Create original layouts with text and graphics for custom T-shirts, labels and decals.



R-Works System Requirements Windows® 7 Professional/Ultimate (32-bit); Windows Vista® Business/Ultimate (32-bit); Windows® XP Professional Service Pack 2 or later (32-bit)

Specifications			C
Printing technology		Piezoelectric inkjet	Т
	Width	150 to 515 mm (5.9 to 20.3 in.)	
<b></b>	Thislesse	Maximum 1.0 mm (39 mil) with liner, for printing	
	Thickness	Maximum 0.4 mm (16 mil) with liner and 0.22 mm (9 mil) without liner, for cutting	
Media	Roll outer diameter	Maximum 150 mm (5.9 in.)	
	Roll weight	Maximum 6 kg (13.2 lbs.)	-
	Core diameter	76.2 mm (3 in.) or 50.8 mm (2 in.)	_
Printing/cutting width*1		Maximum 480 mm (18.9 in.)	E
	Type and capacity	Roland ECO-SOL MAX (220 cc cartridge) or Roland aqueous pigment (FPG) ink (220 cc cartridge)	
		Five colors (cyan, magenta, yellow, black, and metallic silver) or	
Ink cartridges	Colors	Four colors (cyan, magenta, yellow, and black)	
		(Five colors are only ECO-SOL MAX)	
Printing resolution (dpi)		Maximum 1,440 dpi	
	Type	Roland CAMM-1 series compatible	
Cutting blade	Blade offset	0.25 mm (9 mil)	
Cutting speed		10 to 150 mm/s	
Blade force		30 to 300 gf	Α
Software resolution (when cutting)		0.025 mm/step	
Distance accuracy (when printing) *2 *3		Error of less than ±0.3% of distance traveled, or ±0.3 mm, whichever is greater	
Distance accuracy (when cutting) *2 *4		Error of less than ±0.4% of distance traveled, or ±0.3 mm, whichever is greater	_
Repetition accuracy (when cutting) *2 *5		±0.1 mm or less	
Alignment accuracy for printing and cutting *2 *6		±0.5 mm or less	
Alignment accuracy for printing and cutting		Error of less than ±0.5% of distance traveled, or	E
when reloading media *2 *7		±3 mm, whichever is greater	
Print heater *8		Temperature: 35°C (95°F)	
Connectivity		USB (compliant with Universal Serial Bus Specification Revision 2.0)	_
Power-saving function / F	ower requirements	Automatic sleep feature / AC 100 to 240 V ±10 %, 1.5 A, 50 / 60 Hz	
•	During operation	Approx. 90 W	Α
Power consumption	Sleep mode	Approx. 5.5 W	
Acoustic noise level	During operation	62 dB (A) or less	
	During standby	42 dB (A) or less	В
Dimensions / Weight		995 (W) x 585 (D) x 291 (H) mm (39.2 (W) x 23 (D) x 11.5 (H) in.) / 35 kg (79.4 lbs.)	В
	Power on	Temperature: 20 to 32°C (68 to 90°F), humidity: 35 to 80%RH (no condensation)	-
Environmental	Power off	Temperature: 5 to 40°C (41 to 104°F), humidity: 20 to 80%RH (no condensation)	
Included items		Power cord, USB cable, blade, blade holder, Roland Software Package.	
		Software RIP (Roland VersaWorks), User's Manual, etc.	

1 The length of printing or cutting is subject to the limitations of the program, \*2 Using Roland specified media, loaded correctly, temperature \*1 The length of printing or cutting is subject to the limitations of the program. \*2 Using Roland specified media, loaded correctly, temperature: 25°C (77°F), humidity: 50 %-RH, all pinch rollers are used, 25 mm or more for both right and left margins and 35 mm or more front margin, excluding expansion or contraction of the media, and all correction and adjustment functions of this machine have been made properly. \*3 Using Roland specified media, cut travel of 1m. \*5 Range for assured repetition accuracy: Length 1,000 mm \*6 Provided that media length is under 1,000 mm. Excluding possible shift caused by expansion/cattoin of the media and/or by reloading the media. \*7 Using Roland specified media, data size: 1,000 mm in the media-feed direction, 480 mm in the carriage-movement direction. No lamination. Automatic detection of crop marks at 4 points when media is reloaded. Excludes the effects of skewed movement and of expansion and contraction of the media. \*3 Warm-up is required after power up. This may require 5 to 20 minutes, depending on the operating environment. The preset temperature may fail to be reached 35°C (95°F) depending on the ambient temperature and media width.

Options	Model	Description
	SCM-GVWG-25-508	Coated vinyl white gloss, 508 mm x 25 m (20" x 82')
	MV-G-18G	Gray adhesive vinyl, 460 mm x 20 m (18.11" x 65')
	SCM-GPPG-25-508	Photo paper gloss, 265 gsm, 508 mm x 25 m (20" x 82")
	SCM-GPPM-25-508	Photo paper matt, 265 gsm, 508 mm x 25 m (20" x 82')
	SCM-TTRH-25-500	Textile heat transfer film, 500 mm x 25 m (19.68" x 82')
	SCM-FTRH-25-500	Textile heat transfer film, 500 mm x 25 m (19.68' x 82')
ECO-SOL MAX Media	THT-440	Textile heat transfer film, 440 mm x 20 m (17.32" x 65")
FCO-20T MAY Media	SCM-GGPET-20-500	Glossy gold self adhesive PET, 500 mm x 20 m (19.68" x 65')
	SCM-GSPET-20-500	Glossy silver self adhesive PET, 500 mm x 20 m (19.68" x 65"
	SP2-SG-18T	Glossy PET film, adhesive, 450 mm x 20 m (17.71" x 65")
	SP-CL-515T	Clear PET film, adhesive, 515 mm x 20 m (20.27" x 65')
	RMC-BPBB-45-508	Blueback paper, 135 gsm, 508 mm x 45.7 m (20" x 150')
	RMC-BPWB-45-508	Whiteback paper, 135 gsm, 508 mm x 45.7 m (20" x 150")
	RMC-SAMP	Self adhesive paper, 200 gsm, 508 mm x 30 m (20" x 98')
	PCM-PMP1-30-508	Poster paper, 125 gsm, 508 mm x 30.3 m (20" x 99")
	PCM-PMP2-30-508	Premium matt paper, 150 gsm, 508 mm x 30.48 m (20" x 10
Aqueous Ink Media	PCM-PMP3-30-508	Poster paper, 180 gsm, 508 mm x 30.5 m (20" x 100")
	PCM-WMWV-12-508	Self adhesive vinyl, 508 mm x 12.2 m (20" x 40")
	PCM-SAMP-30-508	Self adhesive paper, 200 gsm, 508 mm x 30 m (20" x 98")
	ESL3-MG	Magenta, 220 cc
	ESL3-YE	Yellow, 220 cc
ECO-SOL MAX Ink	ESL3-CY	Cyan, 220 cc
ECO-SOL MAX IIIK	ESL3-BK	Black, 220 cc
	ESL3-MT	Metallic silver, 220 cc
	SL-CL	Cleaning liquid, 1 pc.
	FPG-MG	Magenta, 220 cc
	FPG-YE	Yellow, 220 cc
Aqueous Pigment Ink	FPG-CY	Cyan, 220 cc
	FPG-BK	Black, 220 cc
	CJ-CL	Cleaning liquid, 1 pc.
Blade	ZEC-U5022	For thick, reflective and fluorescent vinyl, 2pcs.
Blade holder XD-CH3		Blade holder with blade extension abjuster, made of resin



About Metallic Silver Ink

Due to the nature of the metallic silver ink, the pigment in this ink will settle in the cartridge and ink flow system, requiring you to shake the cartridge before each use. Outdoor durability is three years for CMYK inks, one to three years metallic silver ink, depending on the media used. Roland strongly recommends lamination for both indoor and outdoor graphics to ensure the quality of metallic silver ink.

Roland DG products that feature this environmental label meet the company's criteria for environmental consciousness, a set of standards based on ISO 14021 self-declaration type II. For more information, please visit www.rolanddg.com.



#### ISO 14001:2004 and ISO 9001:2008 Certified

Roland pursues both environmental protection and continuous quality improvement. Under the philosophy of preserving the environment and human health, Roland is actively working to abolish organic solvents in production, to reduce and recycle waste, to reduce power use, and to purchase recycled products. Roland constantly strives to provide the most highly reliable products



Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Adobe, PostScript, PostScript 3 and the PostScript fogo are trademarks of Adobe Systems Incorporated. All other trademarks are the property of their respective owners. Roland DG Corp. has licensed the MMP technology from the TPL Group.



#### Roland DG North Europe A/S

Engholm Parkvej 5 DK-3450 Allerod T: +45 88 82 20 00

www.rolanddg.eu





instagram.com/rolanddgn





facebook.com/RolandDGN

Imagine.





# VersaSTUDIO SIGN MAKER BN-20

## **Make a Lasting Impression** with VersaSTUDIO











